

424-LRX* Specifications

Minimum seat height (ADA Compliant):	Low Model 19" (48.3 cm)
	High Model 21" (53.3 cm)
Maximum seat height:	Low Model 30.5" (77.5 cm)
	High Model 37" (94 cm)
Maximum vertical elevation:	Low Model 11.5" (29.2 cm)
	High Model 16" (40.6 cm)
Section Dimensions	
Back Section:	19" tapering to 13" wide x 21" long (48.3 cm tapering to 33 cm wide x 53 cm long)
Seat Section:	19.5" wide x 19" deep (49.5 cm wide x 48.3 cm)
Foot Section:	
High Model	19" tapering to 13" wide x 18.5" long (48.3 cm tapering to 33 cm wide x 47 cm)
Low Model	19" tapering to 13" wide x 16" long (48.3 cm tapering to 33 cm wide x 40.6 cm)
Maximum width between arms:	19" (48.3 cm)
Maximum width w/arms:	26" (66 cm)
Maximum Trendelenburg:	15°
Overall length†:	
High Model w/o headrest extension	68" (173 cm)
High Model w/headrest extension	74" (188 cm)
Low Model w/o headrest extension	65.5" (166 cm)
Low Model w/headrest extension	71.5" (181.6 cm)
Electrical Input/Power Consumption:	115/60, 4.8 amps
	230/50, 2.4 amps
Weight†:	308 lbs (140 kg)
Shipping weight†:	372 lbs (169 kg)
Shipping size:	80" x 32" x 34" (203 cm x 81 cm x 86 cm)

Listed to the Safety Standards for Medical Electrical Equipment UL 60601-1, CSA-C22.2 60601-1, and IEC 60601-1.

†Will vary depending on options chosen.

