

# 430 Series\* Specifications

Minimum seat height:	Low Model 19" (48.3 cm)
	High Model 21" (53.3 cm)
Maximum seat height:	Low Model 33" (83.8 cm)
	High Model 39.5" (100.3 cm)
Max. vertical elevation:	Low Model 11.5" (29.2 cm)
	High Model 16" (40.6 cm)
<b>Section Dimensions</b>	
<b>Tapered Back Section:</b>	
428:	20" tapering to 8" wide x 22" long (50.8 cm tapering to 20.3 cm wide x 55.9 cm long)
429:	22" tapering to 10" wide x 22" long (55.9 cm tapering to 25.4 cm wide x 55.9 cm long)
430:	24" tapering to 12" wide x 22" long (61 cm tapering to 30.5 cm wide x 55.9 cm long)
<b>Square Back Section:</b>	
429:	22" wide x 22" long (55.9 cm x 55.9 cm)
430:	24" wide x 22" long (70 cm x 55.9 cm)
<b>Seat Section:</b>	
428:	20" wide x 20.5" deep (50.8 cm wide x 52.1 cm)
429:	22" wide x 20.5" deep (55.9 cm x 52.1 cm)
430:	24" wide x 20.5" deep (61 cm x 52.1 cm)
<b>Foot Section:</b>	
428:	20" tapering to 17" wide x 17" deep (50.8 cm tapering to 43.2 cm wide x 43.2 cm)
429:	22" tapering to 19" wide x 17" deep (55.9 cm tapering to 48.3 cm wide x 43.2 cm)
430:	24" tapering to 21" wide x 17" deep (61 cm tapering to 58.3 cm wide x 43.2 cm)
Maximum Trendelenburg:	30°
Overall length:	w/o headrest extension 71" (180.3 cm)
	w/headrest extension 77" (195.6 cm)
<b>Electrical Input/Power Consumption:</b>	
Quad Power models:	115/60, 5.3 amps
	230/50, 2.65 amps
Tri Power, coordinated back/foot models:	115/60, 4.3 amps
	230/50, 2.15 amps
<b>Weight†:</b>	
428:	336 lbs (152 kg)
429:	341 lbs (155 kg)
430:	349 lbs (158 kg)
<b>Shipping weight†:</b>	
428:	410 lbs (186 kg)
429:	415 lbs (188 kg)
430:	423 lbs (192 kg)
<b>Shipping size†:</b>	
428/429/430	80" x 32" x 34" (203 cm x 81 cm x 86 cm)

Listed to the Safety Standards for Medical Electrical Equipment UL 60601-1, CSA-C22.2 60601-1, and IEC 60601-1.

†Will vary depending on options chosen.

